

EVINRUDE® E-TEC® G2®

# 300 HP

## SPECIFICATIONS

<b>Engine Type</b>	V6 74° E-TEC G2 D.I.
<b>Bore x Stroke - in (mm)</b>	3.85 x 3.00 (98 x 76)
<b>Displacement - cu in (L)</b>	210 (3.4L)
<b>Gear Ratio</b>	1.85:1
<b>Full Throttle RPM Range</b>	5400-6000 RPM
<b>Starting</b>	Electric
<b>Controls</b>	ICON II
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	133 Amps Total / 50 net Dedicated / 14 amps @ idle
<b>Trim Method</b>	Power Trim & Tilt
<b>Trim Range</b>	-6° to 15°
<b>Tilt Range</b>	81°
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - gal (L)</b>	On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
<b>Recommended Oil</b>	XPS Marine XD100
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	5-Year Engine** / 5-Year Corrosion
<b>Mounting Centers - in (mm)</b>	Minimum 28 (711)
<b>Color Customization</b>	Over 400 Color Panel Options
<b>Steering Angle</b>	+/- 30°
<b>Integrated Features</b>	Dual Axis Rigging / iTrim
<b>100% Global Emissions Compliant</b>	EPA 2013 / CARB 3 STAR / European Union



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)	
Single	Slate Gray	20 (508)	iSteer DPS	H300GLF	547 (248)	
	Classic White	20 (508)	iSteer DPS	H300WLF	547 (248)	
Single / Multiple	Slate Gray	25 (635)	iSteer DPS / IHS / Tiebar	H300GXF† H300GXC‡	558 (253) 558 (253)	
			iDOCK / iDOCK	H300GXA H300GXCA‡	558 (253) 558 (253)	
			iSteer DPS / IHS / Tiebar	H300WXF† H300WXC‡	558 (253) 558 (253)	
			Optimus 360 / IHS / IHS / Tiebar	H300WXI H300WXC‡	558 (253) 558 (253)	
	Classic White	25 (635)	iDOCK / iDOCK	H300WXA H300WXCA‡	558 (253) 558 (253)	
			iSteer DPS / IHS / Tiebar	H300WZF† H300WZC‡	570 (259) 570 (259)	
			Optimus 360 / IHS / IHS / Tiebar	H300WZI H300WZC‡	570 (259) 570 (259)	
			iDOCK / iDOCK	H300WZA H300WZCA‡	570 (259) 570 (259)	
			30 (762)	iSteer DPS / IHS / Tiebar	H300WZF† H300WZC‡	570 (259) 570 (259)
				Optimus 360 / IHS / IHS / Tiebar	H300WZI H300WZC‡	570 (259) 570 (259)

\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

† Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK and Optimus 360 models available for multiple installation only.

‡ Corresponding Counter Rotation model.

Specifications subject to change.

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

**EVINRUDE®**