

EVINRUDE® E-TEC®

115 H.O.

SPECIFICATIONS

Engine Type	H.O. V4 60° E-TEC D.I.
Bore x Stroke - in (mm)	3.62 x 2.60 (92 x 66)
Displacement - cu in (L)	105.4 (1.7)
Gear Ratio	2.00:1
Full Throttle RPM Range	5500-6000 RPM
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	133 Amps Total / 50 Net Dedicated
Steering	Remote (Tiller accessory)
Trim Method	Trac-1 Power Trim and Tilt
Trim Range	-4° to 17°
Tilt Range	75°
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	Accessory 1.8 (6.8) 3 (11.3) & 10 (37.85) Tank Available
Recommended Oil	XPS Marine XD100 / XD50
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	MODEL NO.	WEIGHT - lb (kg)
Graphite	20 (508)	A115GHL	390 (177)
White	20 (508)	A115SHL	390 (177)

* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp. Specifications subject to change.
©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE