EVINRUDE® E-TEC® G2®

200 H.O.

SPECIFICATIONS			
Engine Type	H.O. V6 74° E-TEC G2 D.I.		
Bore x Stroke - in (mm)	3.85 x 3.00 (98 x 76)		
Displacement - cu in (L)	210 (3.4L)		
Gear Ratio	1.85:1		
Full Throttle RPM Range	5400-6000 RPM		
Starting	Electric		
Controls	ICON II		
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode		
Alternator Output*	133 Amps Total / 50 net Dedicated / 14 amps @ idle		
Trim Method	Power Trim & Tilt		
Trim Range	-6° to 15°		
Tilt Range	81°		
Lubrication	Multi-Point Targeted Oiling		
Oil Tank Capacity - gal (L)	On-Engine 2 (7.5) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)		
Recommended Oil	XPS Marine XD100		
Recommended Fuel	87 Octane		
Warranty	5-Year Engine** / 5-Year Corrosion		
Mounting Centers - in (mm)	Minimum 28 (711)		
Color Customization	Over 400 Color Panel Options		
Steering Angle	+/- 30°		
Integrated Features	Dual Axis Rigging / iTrim		
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union		



INSTALLATION	COLOR	SHAFT LENGTH - in. (mm)	STEERING	MODEL NO.	WEIGHT - lb (kg)
Single ———	Slate Gray	20 (508)	iSteer DPS	H200HGLF	547 (248)
	Classic White	20 (508)	iSteer DPS	H200HWLF	547 (248)
Single [†] / Multiple	Clata Out	05 (605)	iSteer DPS IHS / Tiebar	H200HGXF [†] H200HGXC [‡]	558 (253) 558 (253)
	Slate Gray	25 (635)	iDOCK iDOCK	H200HGXA H200GXCA‡	558 (253) 558 (253)
	Classic White	05 (635)	iSteer DPS IHS / Tiebar	H200HWXF† H200HWXC‡	558 (253) 558 (253)
		25 (635)	iDOCK iDOCK	H200HWXA H200WXCA‡	558 (253) 558 (253)

Specifications subject to change.



Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

^{** 3} years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

[†] Standard Rotation iSteer DPS model available for single and multiple installation. All iDOCK models available for multiple installation only.

[‡] Corresponding Counter Rotation model.