

EVINRUDE® PORTABLES

15 HP

SPECIFICATIONS

Engine Type	2-cylinder
Bore x Stroke - in (mm)	2.4 x 2.36 (61 x 60)
Displacement - cu in (cc)	21.4 (351)
Gear Ratio	2.15:1
Full Throttle RPM Range	5000-6000 RPM
Controls	Mechanical
Fuel Induction	Carbureted
Steering	Tiller
Trim Method	Manual or Power Tilt
Oil Tank Capacity - fl oz (ml)	32 (950)
Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union



COLOR	SHAFT LENGTH - in. (mm)	STARTING	ALTERNATOR OUTPUT	MODEL NO.	WEIGHT - lb (kg)
Graphite	15 (381)	Manual	N/A	E15RG4	114.4 (52)
		Electric	12V, 145W, 12A	E15TEG4	120 (55)
	20 (508))	Manual	N/A	E15RGL4	117 (53)

Specifications subject to change.
 ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

